

Hybrid Wall Outlet

4 Plus 4



Description

The hybrid wall outlet (4 PLUS 4) features two keystone breakouts for standard copper applications, as well as additional capacity for up to four fibre optic adapters. This makes the outlet particularly well suited for use in hybrid cabling environments, eliminating the need for installation of an additional outlet for a second medium. The outlet is optimised for FTTH networks and wherever fibre cable is installed in parallel to or as replacement for copper cable.

Features and Benefits

- Surface, flush or wall duct mounting
- Two keystone breakouts for at least four copper pairs
- Additional breakouts for four fibre terminations
- Integrated molded splice areas
- Lockable cover
- Optimised for network expansion projects
- Supports blown-fibre installations

Installation

The wall outlet supports two RJ11 or RJ45 jacks for copper-based data lines, as well as up to four SC simplex or two LC/SC duplex fibre optic connectors. The outlet can be surface- or flushmounted, or installed on a wall duct. The corresponding cable entries in both the base-plate and the termination plate can be removed as needed. The cover, which snaps closed, can also be fitted with a standard screw or coded screw-locking mechanism to prevent unauthorised access. An additional protective foil covering the locking area serves for further protection from unauthorised access.

TECHNICAL DATA



www.adckrone.com • Technical Assistance Centre: +32 2 712 6542 • euro.tac@adckrone.com

Freephone (UK only): 0800 960236

Product Specifications

MECHANICAL CHARACTERISTICS

Material: Polycarbonate Halogen free / LSZH-1
 Colour: White RAL9010
 Dimensions: 126mm x 93mm x 50mm

Catalogue Number

FTX- 7029 1 2 - 0

Type	Code
Unloaded	0
Loaded	1

Fiber Count

Code	Type
0	No fiber
1	1 fiber
2	2 fiber
4	4 fiber

Loaded with singlemode adapters and pigtails

Type	Code
Unloaded	0
LC/APC	1
LC/UPC	2
SC/APC	3
SC/UPC	4

OR

Loaded with singlemode adapters only

Type	Code
LC/APC	5
LC/UPC	6
SC/APC	7
SC/UPC	8

For Example: Hybrid Wall Outlet, loaded with 2 SC/APC adapters and pigtails FTX-7029 1 132-02.

For ordering keystone jacks please see ADC KRONE's TrueNet® catalogue.

Accessories

Description	Catalogue Number
Standard lock set Rectangular nut and Phillips screw	7029 2 004-00
Standard lock set Rectangular nut and coded screw	7029 2 005-00

TECHNICAL DATA



Web Site: www.adckrone.com

EMEA Office: ADC GmbH, Beeskowdamm, 3-11, 14167 Berlin, Germany • Phone: +49 30 8453-1818 Fax: +49 30 8453-1703. For a listing of all ADC KRONE's global sales office locations, please refer to our web site.

UK Office: ADC Communications (UK) Ltd., Runnings Road, Kingsditch Trading Estate, Cheltenham, Gloucestershire GL51 9NQ, United Kingdom • Phone: +44 (0) 1242 264 400 Fax: +44 (0) 1242 264 488 contactuk@adckrone.com

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC KRONE reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting ADC GmbH headquarters in Berlin. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents.

200809BE Apr 09 Original © 2009 ADC Telecommunications Inc. All Rights Reserved