

# TrueNet®

## Category 5e F/UTP Patch Cord



Shielded TrueNet® Category 5e overmoulded patch cords from ADC KRONE have been 100% tested at a component level (details on reverse).

The patch cord boot has been designed to protect the integrity of the termination within the plug and latch mechanism during Moves Adds and Changes (MACs). Its slim-line design and profile also make it suitable for maximising density at the patch panel and for use in space restricted locations, for example under floor raceway boxes and Multi User Telecommunication Outlet (MUTO) assemblies.

The shielded patch cords are available with either LSZH or PVC sheaths in various core colours, which aid circuit identification within installations.

Shielded TrueNet® Category 5e patch cords are available in standard T568B wiring configuration.

### Features

- 100% tested at a component level
- Shielded design (F/UTP)
- Stranded copper conductors in cable pairs
- Flexible strain relief boot with latch protection
- Fully interoperable and backwards compatible
- Multiple colour options
- Low profile boot design

### Benefits

- Guaranteed component performance
- Superior cable flexibility from stranded cores
- Boot maximises protection during MACs
- Colour options aid circuit identification
- Maximum density where space is restricted
- Part of the end-to-end shielded solution

TECHNICAL DATA





**Technical Assistance:**  
**Europe & Middle East**  
+32 2 712 6542  
euro.tac@adckrone.com  
www.adckrone.com

**South Africa**  
+27 11 466 3333  
infos@adckrone.com

**United Kingdom**  
0800 960236  
contactuk@adckrone.com

## Ordering Information

Description	Cable Colour	Catalogue Number
<b>Category 5e F/UTP Overmoulded Patch Cord LSZH</b> <b>RJ45 plug to RJ45 plug</b> 	Blue F/UTP	7063 2 641-YY
	Red F/UTP	7063 2 642-YY
	Yellow F/UTP	7063 2 643-YY
	Green F/UTP	7063 2 644-YY
	Orange F/UTP	7063 2 645-YY
	Grey F/UTP	7063 2 647-YY
	White F/UTP	7063 2 640-YY
<b>Category 5e F/UTP Overmoulded Patch Cord PVC</b> <b>RJ45 plug to RJ45 plug</b> 	Blue F/UTP	7063 2 631-YY
	Red F/UTP	7063 2 632-YY
	Yellow F/UTP	7063 2 633-YY
	Green F/UTP	7063 2 634-YY
	Orange F/UTP	7063 2 635-YY
	Grey F/UTP	7063 2 637-YY
	White F/UTP	7063 2 630-YY

Replace YY with:

04 = 1m      10 = 3m      25 = 7.5m  
 07 = 2m      15 = 5m      33 = 10m

Contact ADC KRONE for additional cable colours and lengths.

### Technical Data

Operating temperature range:	-10°C to 60°C
RJ45 plug interface according to:	IEC 60603-7 Series (=750 mechanical operations)
Transmission performance and reliability:	TIA-568-B.2 Category 5e ISO/IEC 11801:2002 Category 5 EN 50173-1:2007 Category 5 IEC/EN 61935-2
Conductor:	26 (7x32) AWG stranded copper
Jacket:	LSZH (EN 60754-1 & -2)
Nominal outer diameter:	5.5mm
Safety rating:	IEC/EN 60950 LVD compliant
Flammability rating:	IEC 60332-1
Testing requirements of connection technology according to ISO/IEC 11801 2nd Edition, ANSI/TIA/EIA-568-B.2 and EN 50173:2007.	
All connecting hardware is tested individually and as part of a channel to ensure critical parameters of Powersummation, ACR-N, NEXT, ACR-F and Return Loss exceed the requirements specified in international standards.	

TECHNICAL DATA



**Web Site:** [www.adckrone.com](http://www.adckrone.com)

**UK Office:** ADC Communications (UK) Ltd., Runnings Road, Kingsditch Trading Estate, Cheltenham, Gloucestershire GL51 9NQ, United Kingdom • Phone: +44 (0) 1242 264 400 Fax: +44 (0) 1242 264 488 [contactuk@adckrone.com](mailto:contactuk@adckrone.com)

**South African Office:** ADC Telecommunications (Africa) PTY Ltd., 16 Brand Hatch Close, Kyalami Business Park, Midrand, 1685, Johannesburg, South Africa • Phone: +27 11 466 3333 Fax: +27 11 466 3300 Email: [infos@adckrone.com](mailto:infos@adckrone.com)

**EMEA Office:** ADC GmbH, Beeskowdamm, 3-11, 14167 Berlin, Germany • Phone: +49 30 8453 1818 Fax: +49 30 8453 1703. For a listing of all ADC KRONE's global sales office locations, please refer to our web site.

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC KRONE reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting ADC GmbH headquarters in Berlin. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents.

**200992BE June 09 Original © 2009 ADC Communications (UK) Ltd. All Rights Reserved.**